

Secretariat

Distr. GENERAL

ST/SG/AC.10/C.4/2002/16/Add.5 1 October 2002

Original: ENGLISH

COMMITTEE OF EXPERTS ON THE TRANSPORT OF DANGEROUS GOODS AND ON THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS

Sub-Committee of Experts on the Globally Harmonized System of Classification and Labelling of Chemicals (Fourth session, 9-11 December 2002 agenda item 2)

GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)

Submitted by the GHS Editorial Group

Annex 2

Classification and Labelling Summary Tables

[Blank page]

Annex 2
Classification and labelling summary tables

A2.1 Explosives (see Chapter 2.1 for details)

Hazard category	Criteria	Hazard communic	cation elements
Division 1.1	According to the results of the test in Part I of the Manual of Tests and Criteria, UN	Symbol	
DIVISION IVI	Recommendations on the	Signal word	Danger
	Transport of Dangerous Goods.	Hazard statement	Explosive; mass explosion hazard
	According to the results of the test in Part I of the Manual of	Symbol	
Division 1.2	Tests and Criteria, UN Recommendations on the	Signal word	Danger
	Transport of Dangerous Goods	Hazard statement	Explosive; severe projection hazard
Division 1.3	According to the results of the test in Part I of the Manual of Tests and Criteria, UN Recommendations on the Transport of Dangerous Goods	Symbol	
		Signal word	Danger
		Hazard statement	Explosive; fire, blast or projection hazard
Division 1.4	According to the results of the test in Part I of the Manual of Tests and Criteria, UN Recommendations on the Transport of Dangerous Goods	Symbol	1.4
		Signal word	Warning
		Hazard statement	Fire or projection hazard
Division 1.5	According to the results of the test in Part I of the <i>Manual of</i>	Symbol	1.5
Division 1.5	Tests and Criteria , UN Recommendations on the	Signal word	Warning
	Transport of Dangerous Goods.	Hazard statement	May explode in fire
Division 1.6	According to the results of the test in Part I of the Manual of Tests and Criteria, UN	Symbol	1.6
217151011 1.0	Recommendations on the	Signal word	No signal word
	Transport of Dangerous Goods	Hazard statement	No hazard statement

A2.2. Flammable gases (See Chapter 2.2 for details)

Hazard category	Criteria	Hazard communication elements	
1	Gases and gas mixtures, which at 20 °C and a standard pressure of 101.3 kPa: (a) are ignitable when in a mixture of 13% or less by volume in air; or	Symbol	
	(b) have a flammable range with air of at least 12 percentage points regardless of the lower	Signal word	Danger
	flammable limit.	Hazard statement	Extremely flammable gas
	Gases or gas mixtures, other than those of category	Symbol	No symbol used
2	1, which, at 20 °C and a standard pressure of	Signal word	Warning
	101.3 kPa, have a flammable range while mixed in air.	Hazard statement	Flammable gas

A2.3 Flammable aerosols (See Chapter 2.3 for details)

Hazard category	Criteria	Hazard communication elements	
	On the basis of its components, of its chemical heat of	Symbol	
1	combustion and, if applicable, of the results of the foam test, for foam aerosols, and of the ignition distance test and enclosed space test, for spray aerosols (see decision logic in 2.3.4.1 of Chapter 2.3).	Signal word	Danger
		Hazard statement	Extremely flammable aerosol
2	On the basis of its components, of its chemical heat of combustion and, if applicable, of the results of the	Symbol	
2	foam test, for foam aerosols, and of the ignition distance test and enclosed space test, for spray	Signal word	Warning
	aerosols (see decision logic in 2.3.4.1 of Chapter 2.3).	Hazard statement	Flammable aerosol

A2.4 Oxidizing gases (See Chapter 2.4 for details)

Hazard category	Criteria	Hazard commun	ication elements
1	Any gas which may, generally by providing oxygen, cause or contribute to the combustion of other material more than air does.	Symbol	
		Signal word	Danger
		Hazard statement	May cause or intensify fire; oxidizer

A2.5 Gases under pressure (See Chapter 2.5 for details)

Hazard category	Criteria		ommunication ements
		Symbol	
Compressed gas	A gas, which when packaged under pressure is entirely gaseous at -50 °C; including all gases with a critical temperature ≤ -50 °C.	Signal word	Warning
	temperature 2 - 30°C.	Hazard statement	Contains gas under pressure; may explode if heated
	A gas which when packaged under pressure, is partially liquid at temperatures above -50 °C. A distinction is made between:	Symbol	
Liquefied gas	 i) High pressure liquefied gas: a gas with a critical temperature between -50 °C and +65 °C; and ii) Low pressure liquefied gas: a gas with a critical temperature above +65 °C. 	Signal word	Warning
		Hazard statement	Contains gas under pressure; may explode if heated
	A gas which when packaged is made partially liquid because of its low temperature.	Symbol	
Refrigerated		Signal word	Warning
liquefied gas		Hazard statement	Contains refrigerated gas; may cause cryogenic burns or injury
		Symbol	
Dissolved gas	A gas which when packaged under pressure is dissolved in a liquid phase solvent.	Signal Word	Warning
	dissorted in a riquid phase sortent.	Hazard statement	Contains gas under pressure; may explode if heated

A2.6 Flammable liquids (See Chapter 2.6 for details)

Hazard category	Criteria	Hazard communication elements	
1	Flash point < 23 °C and	Symbol	
	initial boiling point \leq 35 °C	Signal word	Danger
		Hazard statement	Extremely flammable liquid and vapour
2	Flash point < 23 °C and initial boiling point >35 °C	Symbol	
2		Signal word	Danger
		Hazard statement	Highly flammable liquid and vapour
3	Flash point ≥ 23 °C and ≤ 60 °C	Symbol	
		Signal word	Warning
		Hazard statement	Flammable liquid and vapour
		Symbol	No symbol used
4	Flash point > 60 °C and ≤ 93 °C	Signal word	Warning
		Hazard statement	Combustible liquid

A2.7 Flammable solids (See Chapter 2.7 for details)

Hazard category	Criteria		Hazard comm	nunication elements
1	Burning rate test: Substances other than metal - wetted zone does not ste - burning time < 45 s	-	Symbol	
1	burning rate > 2.2 Metal powders:		Signal word	Danger
	- burning time ≤ 5 minutes	Hazard statement	Flammable solid	
	Burning rate test: Substances other than metal - wetted zone stops the fi 4 minutes and	re for at least	Symbol	
2	6	econds or mm/second	Signal word	Warning
	- burning time > 5 m	nutes ninutes	Hazard statement	Flammable solid

A2.8 Self-reactive substances (See Chapter 2.8 for details)

Hazard category	Criteria	Hazard communication elements	
	According to the results of tests in the UN Recommendations on the Transport of	Symbol	
Type A	Dangerous Goods, Manual of Tests and Criteria, Part II and the application of the	Signal word	Danger
	decision logic under 2.8.4.1 of Chapter 2.8.	Hazard statement	Heating may cause an explosion
Type B	According to the results of tests in the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.8.4.1 of Chapter 2.8.	Symbol	
		Signal word	Danger
		Hazard statement	Heating may cause a fire or explosion
Type C and D	According to the results of tests in the <i>UN</i> Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.8.4.1 of Chapter 2.8.	Symbol	
and D		Signal word	Danger
		Hazard statement	Heating may cause a fire
Type E and F	According to the results of tests in the <i>UN</i> Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the application of the	Symbol	
	decision logic under para. 2.8.4.1 of	Signal word	Warning
	Chapter 2.8.	Hazard statement	Heating may cause a fire
	According to the results of tests in the UN Recommendations on the Transport of	Signal word	
Type G	Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.8.4.1 of Chapter 2.8.	Symbol	There are no label elements allocated to this hazard
		Hazard statement	category.

A2.9 Pyrophoric liquids (See Chapter 2.9 for details)

Hazard category	Criteria	Hazard communication elements	
	The liquid ignites within 5 min when added to an inert carrier and exposed to air, or it ignites or chars a filter paper on contact with air within 5 min.	Symbol	
1	with an within 3 mm.	Signal word	Danger
		Hazard statement	Catches fire spontaneously if exposed to air

A2.10 Pyrophoric solids (See Chapter 2.10 for details)

Hazard category	Criteria	Hazard communication elements	
		Symbol	
1		Signal word	Danger
		Hazard statement	Catches fire spontaneously if exposed to air

A2.11 Self-heating substances (See Chapter 2.11 for details)

Hazard category	Criteria	Hazard communication elements	
1	A positive result is obtained in a test using	Symbol	
1	a 25 mm sample cube at 140 °C	Signal word	Danger
		Hazard statement	Self-heating; may catch fire
2	(a) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C and the substance is to be packed in packages with a volume of more than 3 m ³ ; or	Symbol	
	(b) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C, a positive result is obtained in a test using a 100 mm cube sample at	Signal word	Warning
	 120 °C and the substance is to be packed in packages with a volume of more than 450 litres; or (c) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C and a positive result is obtained in a test using a 100 mm cube sample at 100 °C 	Hazard statement	Self-heating in large quantities; may catch fire

A2.12 Substances, which on contact with water, emit flammable gases (See Chapter 2.12 for details)

Hazard category	Criteria	Hazard communication elements		
	Any substance which reacts vigorously with water at ambient temperatures and demonstrates generally a tendency for the	Symbol		
1	gas produced to ignite spontaneously, or which reacts readily with water at ambient	Signal word	Danger	
1	temperatures such that the rate of evolution of flammable gas is equal to or greater than 10 litres per kilogram of substance over any one minute.	Hazard statement	In contact with water releases flammable gases which may ignite spontaneously	
2	Any substance which reacts readily with water at ambient temperatures such that the maximum rate of evolution of flammable gas is equal to or greater than 20 litres per kilogram of substance per hour, and which does not meet the criteria for category 1.	Symbol		
		Signal word	Danger	
		Hazard statement	In contact with water releases flammable gases	
3	Any substance which reacts slowly with water at ambient temperatures such that the maximum rate of evolution of flammable	Symbol		
	gas is equal to or greater than 1 litre per kilogram of substance per hour, and which	Signal word	Warning	
	does not meet the criteria for categories 1 and 2.	Hazard statement	In contact with water releases flammable gases	

A2.13 Oxidizing liquids (See Chapter 2.13 for details)

Hazard category	Criteria	Hazard communication elements			
1	Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, spontaneously ignites; or the mean pressure rise time of a 1:1 mixture, by mass, of	Symbol			
	substance and cellulose is less than that of a	Signal word	Danger		
	1:1 mixture, by mass, of 50% perchloric acid and cellulose.	Hazard statement	May cause fire or explosion; strong oxidizer.		
2	Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, exhibits a mean pressure rise time less than or equal to the mean pressure rise time of a 1:1 mixture, by mass, of 40% aqueous sodium chlorate solution and cellulose; and the criteria for category 1 are not met.	Symbol			
		Signal word	Danger		
		Hazard statement	May intensify fire; oxidizer.		
3	Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, exhibits a mean pressure rise time less than or equal to the mean pressure rise time of a 1:1 mixture, by mass, of 65% aqueous nitric acid and cellulose; and the criteria for categories 1 and 2 are not met.	Symbol			
		Signal word	Warning		
		Hazard statement	May intensify fire; oxidizer.		

A2.14 Oxidizing solids (See Chapter 2.14 for details)

Hazard category	Criteria	Hazard co	mmunication elements
1	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time less than the mean burning time of a 3:2	Symbol	
	mixture, by mass, of potassium bromate and cellulose.	Signal word	Danger
		Hazard statement	May cause fire or explosion; strong oxidizer
2	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time equal to or less than the mean burning time of a 2:3 mixture (by mass) of potassium bromate and cellulose and the criteria for category 1 are not met.	Symbol	
		Signal word	Danger
		Hazard statement	May intensify fire; oxidizer
3	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time equal to or less than the mean burning time of a 3:7 mixture (by mass) of potassium bromate and cellulose and the criteria for categories 1 and 2 are not met.	Symbol	
		Signal word	Warning
		Hazard statement	May intensify fire; oxidizer

A2.15 Organic peroxides (See Chapter 2.15 for details)

Hazard category	Criteria	Hazard cor	nmunication elements
Type A	According to the results of test series A to H in the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the	Symbol	
Type A	application of the decision logic under	Signal word	Danger
	2.15.4.1 of Chapter 2.15.	Hazard statement	Heating may cause an explosion
Type B	According to the results of test series A to H in the <i>UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria</i> , Part II and the application of the decision logic under 2.15.4.1 of Chapter 2.15.	Symbol	
		Signal word	Danger
		Hazard statement	Heating may cause a fire or explosion
Type C	According to the results of test series A to H in the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part II and the	Symbol	
and D	application of the decision logic under	Signal word	Danger
	2.15.4.1 of Chapter 2.15.	Hazard statement	Heating may cause a fire
Type E and F	According to the results of test series A to H in the UN Recommendations on the Transport of Dangerous Good, Manual of Tests and Criteria, Part II and the	Symbol	
	application of the decision logic under	Signal word	Warning
	2.15.4.1 of Chapter 2.15.	Hazard statement	Heating may cause a fire
	According to the results of test series A to H in the <i>UN Recommendations on the</i>	Signal word	
Type G	Transport of Dangerous Goods, Manual	Symbol	There are no label elements allocated to this hazard
	of Tests and Criteria, Part II and the application of the decision logic under 2.15.4.1 of Chapter 2.15.	Hazard statement	category.

A2.16 Corrosive to metals (See Chapter 2.16 for details)

Hazard category	Criteria	Hazard communication elements			
1	Corrosion rate on steel or aluminium surfaces exceeding 6.25 mm per year at a	Symbol			
	test temperature of 55 °C.	Signal word	Warning		
		Hazard statement	May be corrosive to metals		

A2.17 Acute toxicity (See Chapter 3.1 for details)

Hazard category	Criteria	Hazard comn	nunication elements
	$LD_{50} \le 5$ mg/kg bodyweight (oral) $LD_{50} \le 50$ mg/kg bodyweight (skin/dermal)	Symbol	
1	$LC_{50} \leq 100 \text{ ppm (gas)}$	Signal word	Danger
	$LC_{50} \le 0.5 \text{ (mg/l) (vapour)}$ $LC_{50} \le 0.05 \text{ (mg/l) (dust,mist)}$		Fatal if swallowed. (oral)
		Hazard statement	Fatal in contact with skin (dermal) Fatal if inhaled (gas, vapour, dust, mist)
	LD ₅₀ between 5 and less than 50 mg/kg bodyweight (oral)	Symbol	
	LD50 between 50 and less than 200 mg/kg bodyweight (skin/dermal)		
2	LC50 between 100 and less than 500 ppm (gas)	Signal word	Danger
	LC50 between 0.5 and less than 2.0 (mg/l) (vapour)		Fatal if swallowed. (oral)
	LC50 between 0.05 and less than 0.5 (mg/l) (dust, mist)	Hazard Statement	Fatal in contact with skin (dermal)
			Fatal if inhaled (gas, vapour, dust, mist)
	LD ₅₀ between 50 and less than 300 mg/kg bodyweight (oral)	Symbol	
	LD ₅₀ between 200 and less than 1000 mg/kg bodyweight (skin/dermal)	Signal word	Danger
3	LC ₅₀ between 500 and less than 2500 ppm (gas)	Hazard	Toxic if swallowed.
	LC ₅₀ between 2.0 and less than 10.0 (mg/l) (vapour)	statement	(oral)
	LC ₅₀ between 0.5 and less than 1.0 (mg/l) (dust, mist)		Toxic in contact with skin (dermal)
			Toxic if inhaled (gas, vapour, dust, mist)
		Co	ntinued on next page

Hazard category (cont'd)	Criteria	Hazard communication elements		
	LD ₅₀ between 300 and less than 2000 mg/kg bodyweight (oral) LD ₅₀ between 1000 and less than 2000 mg/kg bodyweight (skin/dermal)	Symbol		
4	LC_{50} between 2500 and less than 5000 ppm (gas)	Signal word	Warning	
	LC50 between 10.0 and less than 20.0 (mg/l) (vapour)		Harmful if swallowed. (oral)	
	LC50 between 1.0 and less than 5.0 (mg/l) (dust, mist)	Hazard statement	Harmful in contact with skin (dermal)	
			Harmful if inhaled (gas, vapour, dust, mist)	
		Symbol	No symbol	
	LD ₅₀ between 2000 and 5000 (oral or skin/dermal)	Signal word	Warning	
	For gases, vapours, dusts, mists, LC ₅₀ in the equivalent range of the oral and dermal LD ₅₀ (i.e., between 2000 and 5000 mg/kg bodyweight)	Hazard statement	May be harmful if swallowed (oral)	
5	See also the additional criteria Indication of significant effect in humans Any mortality at Category 4 Significant clinical signs at Category 4 Indication from other studies		May be harmful in contact with skin (dermal) May be harmful if inhaled (gas, vapour, dust, mist)	

A2.18 Skin corrosion/irritation (See Chapter 3.2 for details)

Hazard category	Criteria		ommunication ments
	 For Substances and Tested Mixtures: Human experience showing irreversible damage to the skin; Structure/activity or structure property relationship to a substance or mixture already classified as corrosive; pH extremes of ≤ 2 and ≥ 11.5 including 	Symbol	
1	acid/alkali reserve capacity;	Signal word	Danger
Corrosive Including sub- categories A, B, and C; see Chapter	 Positive results in a valid and accepted <i>in vitro</i> skin corrosion test; or Animal experience or test data that indicate that the substance/mixture causes irreversible damage to the skin following exposure of up to 4 hours (See Table 3.2.1) If data for a mixture are not available, use bridging 	Hazard statement	Causes severe skin burns and eye damage
3.2,	principles in 3.2.3.2.		
Table 3.2.1	3. If bridging principles do not apply,		
	 (a) For mixtures where substances can be added: Classify as corrosive if the sum of the concentrations of corrosive substances in the mixture is ≥ 5% (for substances with additivity); or (b) For mixtures where substances cannot be added:≥ 1%. See 3.2.3.3.4. 		

Hazard category (cont'd)	Criteria		Hazard communication elements	
	 For Substances and Tested Mixtures Human experience or data showing reversible damage to the skin following exposure of up to 4 hours; Structure/activity or structure property relationship to a substance or mixture already classified as an irritant; 	Symbol		
	Positive results in a valid and accepted <i>in vitro</i> skin irritation test; or	Signal word	Warning	
2 Irritant	 Animal experience or test data that indicate that the substance/mixture causes reversible damage to the skin following exposure of up to 4 hours, mean value of ≥ 2.3 < 4.0 for erythema/eschar or for oedema, or inflammation that persists to the end of the observation period, in 2 of 3 tested animals (Table3.2.2). 	Hazard statement	Causes skin irritation	
(applies to all	2. <i>If data for a mixture are not available</i> , use bridging principles in 3.2.3.2.			
authorities)	 3. If bridging principles do not apply, classify as an irritant if: (a) For mixtures where substances can be added: the sum of concentrations of corrosive substances in the mixture is ≥ 1% but ≤ 5%; the sum of the concentrations of irritant substances is ≥ 10%; or the sum of (10 x the concentrations of corrosive ingredients) + (the concentrations of irritant ingredients) is ≥ 10%; or (b) For mixtures where substances cannot be added: ≥ 3%. (See 3.2.3.3.4) 			

Hazard category (cont'd)		Criteria	Hazard communication elements	
	1.	For Substances and Tested Mixtures	Symbol	None
		Animal experience or test data that indicates that the substance/mixture causes reversible damage	Signal word	Warning
		to the skin following exposure of up to 4 hours, mean value of $\geq 1.5 < 2.3$ for erythema/eschar in 2 of 3 tested animals (See Table 3.2.2)	Hazard statement	Causes mild skin
	2.	If data for a mixture are not available and the bridging principles in 3.2.3.2.		irritation
3	3.	If bridging principles do not apply, classify as mild irritant if:		
Mild Irritant		• For mixtures where substances can be added the sum of the concentrations of irritant substances in the mixture is ≥ 1% but ≤ 10%;		
(applies to some authorities)		• For mixtures where substances cannot be added: the sum of the concentrations of mild irritant substances is $\geq 10\%$;		
		• the sum of (10 x the concentrations of corrosive substances) + (the concentrations of irritant substances) is $\geq 1\%$ but $\leq 10\%$; or		
		• the sum of (10 x the concentrations of corrosive substances) + (the concentrations of irritant substances) + (the concentrations of mild irritant substances) is $\geq 10\%$.		

A2.19 Serious eye damage / eye irritation (See Chapter 3.3 for details)

Hazard category		Criteria		ommunication ements
	1.	For Substances and Tested Mixtures	G 1 1	
		 Classification as corrosive to skin; 	Symbol	110 W
		 Human experience or data showing damage to the eye which is not fully reversible within 21 days; 		
		• Structure/activity or structure property relationship to a substance or mixture already classified as corrosive;		
		• pH extremes of < 2 and > 11.5 including buffering capacity;	Signal word	Danger
1		 Positive results in a valid and accepted in vitro test to assess serious damage to eyes; or 	Hazard statement	Causes serious eye damage
Irrever- sible Effects		• Animal experience or test data that the substance or mixture produces either (1) in at least one animal, effects on the cornea, iris or conjunctiva that are not expected to reverse or have not reversed; or (2) in at least 2 of 3 tested animals a positive response of corneal opacity ≥ 3 and/or iritis >1.5. (See Table3.3.1)		
	2.	If data for a mixture are not available, use bridging principles in 3.3.3.2.		
	3.	If bridging principles do not apply,		
		 (a) For mixtures where substances can be added: Classify as Category 1 if the sum of the concentrations of substances classified as corrosive to the skin and/or eye Category 1 substances in the mixture is ≥ 3% or (b) For mixtures where substances cannot be added:≥ 1 See 3.3.3.3.4. 		

Hazard category (cont'd)	Criteria		communication lements
(cont d)	 Substances and tested mixtures Classification as severe skin irritant; Human experience or data showing production of changes in the eye which are fully reversible within 21 days; Structure/activity or structure property relationship to a substance or mixture already classified as an eye irritant; Positive results in a valid and accepted in vitro eye irritation test; or 	Symbol	
	Animal experience or test data that indicate that the substance/mixture produces a positive response in at least	Signal word	Warning
2A	 2 of 3 tested animals of : corneal opacity ≥1, iritis ≥1, or conjunctival edema (chemosis) ≥2 (Table 3.3.2). 2. If data for a mixture are not available, use bridging principles in 3.3.3.2. 	Hazard statement	Causes serious eye irritation
Irritant	 3. If bridging does not apply, classify as an irritant (2A) if: (a) For mixtures where substances can be added: the sum of the concentrations of skin and/or eye Category 1 substances in the mixture is ≥ 1% but ≤ 3%; the sum of the concentrations of eye irritant substances is ≥ 10%; or the sum of (10 x the concentrations of skin and/or eye category 1 substances) + (the concentrations of eye irritants) is ≥ 10% (b) For mixtures where substances cannot be added: the sum of the concentrations of eye irritant ingredients is ≥ 3% (See 3.3.3.3.4) 		
	1. For Substances and tested mixtures	Symbol	No symbol
	 Human experience or data showing production of mild eye irritation; Animal experience or test data that indicate that the lesions one fully reversible within 7 days. (See Table 2.2.2) 	Signal word	Warning
2B Mild Irritant	 are fully reversible within 7 days. (See Table 3.3.2) 2. If data for a mixture are not available, use bridging principles in 3.3.3.2. 3. If bridging does not apply, classify as an irritant (2B) if: (a) For mixtures where substances can be added: the sum of the concentrations of skin and/or eye Category 1 substances in the mixture is ≥ 1% but ≤ 3%; the sum of the concentrations of eye irritant substances is ≥ 10%; or the sum of (10 x the concentrations of skin and/or eye category 1 substances) + (the concentrations of eye irritants) is ≥ 10% (b) For mixtures where substances cannot be added: the 	Hazard statement	Causes eye irritation
	eye category 1 substances) + (the concentrations of eye irritants) is $\geq 10\%$		

A2.20 Respiratory sensitizer (See Chapter 3.4 for details)

Hazard category	Criteria	Hazard communication element	
	For Substances and Tested Mixture If there is human evidence that the individual substance induces specific respiratory hypersensitivity, and/or Where there are positive results from an appropriate	Symbol	New health hazard symbol
	animal test	Signal word	Danger
1	 2. If these mixture meets the criteria set forth in the "Bridging Principles" through one of the following: (a) Dilution (b) Batching (c) Substantially Similar Mixture 3. If bridging principles do not apply, classify if any individual respiratory sensitizer in the mixture has a concentration of: ≥ 1.0% Solid/Liquid ≥ 0.2% Gas 	Hazard statement	May cause allergic or asthmatic symptoms or breathing difficulties if inhaled

A2.21 Skin sensitizer (See Chapter 3.4 for details)

Hazard category	Criteria	Hazard communication element	
	For Substances and tested mixture If there is evidence in humans that the individual substance can induce sensitization by skin contact in a substantial number of persons, or	Symbol	
	Where there are positive results from an appropriate animal test	Signal word	Warning
1	 2. If the mixture meets the criteria set forth in the "Bridging Principles" through one of the following: (a) Dilution (b) Batching (c) Substantially similar mixture 	Hazard Statement	May cause allergic skin reaction
	3. If bridging principles do not apply, Classify if any individual skin sensitizer in the mixture has a concentration of: ≥ 1.0% Solid/Liquid/Gas		

A2.22 Mutagenicity (See Chapter 3.5 for details)

Hazard Category	Criteria for classification	Hazard communication elements		
	Known to induce heritable mutations or regarded as	Symbol	New health hazard symbol	
1 (Both	if it induces heritable mutations in the germ cells of	Signal word	Danger	
1A and 1B)	humans (see criteria in 3.5.2) or mixtures containing ≥0.1 % of such a substance	Hazard statement	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)	
		Symbol	New health hazard symbol	
	Causes concern for man owing to the possibility that it may induce heritable mutations in the germ cells of humans (see criteria in 3.5.2) or mixtures containing ≥1.0 % of such a substance	Signal word	Warning	
2		Hazard Statement	Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)	

A2.23 Carcinogenicity (See Chapter 3.6 for details)

Hazard category	Criteria	Hazard communication elements	
		Symbol	New health hazard symbol
1	Known or Presumed Human	Signal word	Danger
(both 1A and 1B)	Carcinogen including mixtures containing ≥ 0.1% of such a substance	Hazard statement	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard.
		Symbol	New health hazard symbol
		Signal word	Warning
2	Suspected human carcinogen Including mixtures containing more than ≥ 0.1 or ≥1.0 % of such a substance (See Notes 1 and 2 in Table 3.6.1 of Chapter 3.6)	Hazard statement	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard*)

^{*} Some authorities will choose to label according to this provision, others may not.

A2.24 (a) Toxic to reproduction (See Chapter 3.7 for details)

Hazard category	Criteria	Hazard communication elements	
		Symbol	New health hazard symbol
1	Known or presumed human reproductive toxicents (see	Signal word	Danger
1 (Both 1A and 1B)	Known or presumed human reproductive toxicants (see criteria in 3.7.2.2.1 to 3.7.2.6.0 of Chapter 3.7) or mixtures containing ≥ 0.1% or ≥0.3 % of such a substance (See notes 1 and 2 of Table 3.7.1, Chapter 3.7)	Hazard statement	May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
		Symbol	New health hazard symbol
	Suspected human reproductive toxicents (see criteria in	Signal word	Warning
2	Suspected human reproductive toxicants (see criteria in 3.7.2.2.1 to 3.7.2.6.0 of Chapter 3.7) or mixtures containing ≥ 0.1% or ≥3.0 % of such a substance (See Notes 3 and 4 of Table 3.7.1, Chapter 3.7)	Hazard statement	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

A2.24 (b) Effects on or via lactation (See Chapter 3.7)

Hazard category (cont'd)	Criteria	Hazard communication elements	
		Symbol	No symbol
Special category	Substances which cause concern for the health of breastfed children (see criteria in 3.7.2.2.1 to 3.7.2.6.0 and 3.7.3.4 of Chapter 3.7)	Signal word	No signal word
		Hazard Statement	May cause harm to breast-fed children.

A2.25 Target organ systemic toxicity following single exposure (See Chapter 3.8 for details)

Hazard category	Criteria		mmunication ments
		Symbol	New health hazard symbol
1	Reliable evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or systemic toxicity in humans or animals. May use guidance values in Table 3.8.1, Category 1 criteria as part of weight of evidence evaluation. May be named for specific organ/system.] Mixture that lacks sufficient data, but contains Category 1 ingredient at a concentration of ≥ 1.0 to $\leq 10.0\%$ for some authorities; and $\geq 10.0\%$ for all authorities.	Signal word Hazard statement	Danger Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
		Symbol	New health hazard symbol
2	Evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or systemic toxicity from animal studies or humans considering weight of evidence and guidance values in Table 3.8.1, Category 2 criteria. May be named for specific organ/system affected. Mixture that lacks sufficient data, but contains Category 1 ingredient: ≥ 1 but $\leq 10\%$ for some authorities; and /or contains Category 2 ingredient: ≥ 1 to $\leq 10\%$ for some authorities; and $\geq 10\%$ for all authorities	Hazard statement	Warning May causes damage to rgans (state all rgans affected, if known) through prolonged or repeated exposure (state route of xposure if it is conclusively proven that no other routes of exposure cause the hazard)

A2.26 Target organ systemic toxicity following repeat exposure (See Chapter 3.9 for details)

Hazard category	Criteria		ommunication ements
	Reliable evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or	Symbol	New health hazard symbol
1		Signal word Hazard statement	Danger Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure
			(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
	Evidence on the substance or mixture (including bridging)	Symbol	New health hazard symbol
2	Evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or systemic toxicity from animal studies or humans considering weight of evidence and guidance values in Table 3.9.2 criteria. May be named for specific organ/system. Mixture that lacks sufficient data, but contains Category 1 ingredient: ≥ 1.0 but ≤10% for some authorities (See Note 3 of Table 3.9.3) and /or contains Category 2 ingredient: ≥ 1.0 or ≥10%	ignal word Hazard statement	Warning May cause amage to organs (state all organs affected, if known) through prolonged or repeated exposure (state oute of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Hazard category	Criteria	Hazard communication elements	
	 I. For Substances and Tested Mixtures: L(E)C₅₀ ≤ 1mg/L where L(E)C₅₀ is either fish 96hr LC₅₀, crustacea 48hr EC LC₅₀ or aquatic plant 72 or 96hr ErC₅₀ 	Symbol	***************************************
	2. If data for a mixture are not available, use bridging principles (see 3.10.3.4)	Signal word	Warning
1	 3. If bridging principles do not apply, (a) For mixtures with classified ingredients: The <u>summation</u> method (see 3.10.3.10.3.5.5) reveals: •[Concentration of Acute 1] x M > 25% where M is a multiplying factor (see 3.10.3.5.5.5). (b) For mixtures with tested ingredients: The <u>additivity</u> formula (see 3.10.3.5.2 and 3.10.3.5.3) reveals: •L(E)C₅₀ ≤ 1mg/L (c) For mixtures with both classified and tested ingredients: The combined <u>additivity</u> formula and <u>summation</u> method (see paragraphs 3.10.3.5.2 to 3.10.3.5.5.3) reveal: •[Concentration of Acute 1] x M > 25% 4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment". 	Hazard statement	Very toxic to aquatic life

Hazard category (cont'd)	Criteria	Hazard communication elements	
	 1. For Substances and Tested Mixtures: • 1mg/L < L(E)C₅₀ ≤ 10mg/L where L(E)C₅₀ is either fish 96hr LC₅₀, crustacea 	Symbol	No symbol used
	48hr EC LC ₅₀ or aquatic plant 72 or 96hr ErC ₅₀	Signal word	No signal word
2	 48hr EC LC₅₀ or aquatic plant 72 or 96hr ErC₅₀ 2. If data for a mixture are not available, use bridging principles (see 3.10.3.4) 3. If bridging principles do not apply, (a) For mixtures with classified ingredients: The summation method (see 3.10.3.5.5.1 to 3.10.3.5.5.3) reveals: • [Concentration of Acute 1] x M x 10	Hazard statement	Toxic to aquatic life
	or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment".		

Hazard category (cont'd)	Criteria	Hazard communication elements	
(000000)	 1. For Substances and Tested Mixtures: • 10mg/L < L(E)C₅₀ ≤ 100mg/L 	Symbol	No symbol used
	where L(E)C ₅₀ is either fish 96hr LC ₅₀ , crustacea 48hr EC LC ₅₀ or aquatic plant 72 or 96hr ErC ₅₀	Signal word	No signal word
	2. If data for a mixture are not available, use bridging principles (see 3.10.3.4)		
	3. If bridging principles do not apply,		
	(d) For mixtures with classified ingredients: The <u>summation</u> method (see 3.10.3.5.5.1 to 3.10.3.5.5.3) reveals: •[Concentration of Acute 1] x M x 100 +[Concentration of Acute 2] x 10 +[Concentration of Acute 3] > 25% where M is a multiplying factor (see 3.10.3.5.5.5).		
3	(e) For mixtures with tested ingredients: The <u>additivity</u> formula (see $3.10.3.5.2$ - $3.10.3.5.3$) reveals: • $10 \text{mg/L} < L(E)C_{50} \le 100 \text{mg/L}$	Hazard statement	Harmful to aquatic life
	(f)For mixtures with both classified and tested ingredients: The combined <u>additivity</u> formula and <u>summation</u> method (see 3.10.3.5.2 to 3.10.3.5.5.3) reveal: • [Concentration of Acute 1] x M x 100 + [Concentration of Acute 2] x 10 + [Concentration of Acute 3] > 25%		
	4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment".		

A2.28 Chronic hazards to the aquatic environment (See Chapter 3.10 for details)

Hazard category	Criteria	Hazard communication elements	
	 1. For Substances: L(E)C₅₀ ≤ 1mg/L; and Lack the potential to rapidly biodegrade and/or have the potential to bioaccumulate (BCF≥ 500 or if absent log Kow ≥ 4). 	Symbol	***************************************
	where L(E)C ₅₀ is either fish 96hr LC ₅₀ , crustacea 48hr EC LC ₅₀ or aquatic plant 72 or 96hr ErC ₅₀	Signal word	Warning
1	2. For Mixtures, use bridging principles (see 3.10.3.4).		
	 3. If bridging principles do not apply, [Concentration of Chronic 1] x M > 25% where M is a multiplying factor (see 3.10.3.5.5.5). 4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment". 	Hazard statement	Very toxic to aquatic life with long lasting effects
	 1. For Substances: 1 mg/L < L(E)C₅₀ ≤ 10 mg/L; and Lack the potential to rapidly biodegrade and/or have the potential to bioaccumulate (BCF≥ 500) 	Symbol	***
	or if absent log Kow ≥ 4); unless	Signal word	No signal word
2	 Chronic NOECs > 1mg/L 2. For Mixtures, use bridging (see 3.10.3.4). 3. If bridging principles do not apply, [Concentration of Chronic 1] x M x 10 + [Concentration of Chronic 2] > 25% where M is a multiplying factor (see 3.10.3.5.5.5). 4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment". 	Hazard statement	Toxic to aquatic life with long lasting effects

Hazard category (Cont'd)	Criteria	Hazard communication elements	
	 1. For Substances: 10 mg/L < L(E)C₅₀ ≤ 100 mg/L; and 	Symbol	No symbol used
	 Lack the potential to rapidly biodegrade and/or have the potential to bioaccumulate (BCF≥ 500 or if absent log Kow ≥ 4); unless Chronic NOECs > 1mg/L 	Signal word	No signal word
	2. For Mixtures, use bridging principles (see 3.10.3.4).		
3	 3. If bridging principles do not apply, [Concentration of Chronic 1] x M x 100 + [Concentration of Chronic 2] x 10 + [Concentration of Chronic 3] > 25% where M is a multiplying factor (see 3.10.3.5.5.5). 4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment". 	Hazard statement	Harmful to aquatic life with long lasting effects
	1. For Substances:poorly soluble and no acute toxicity is observed	Symbol	No symbol used
	 up the water solubility Lack the potential to rapidly biodegrade and/or have the potential to bioaccumulate (BCF≥ 500 or if absent log Kow ≥ 4); unless Chronic NOECs > 1mg/L 	Signal word	No signal word
4	 2. For Mixtures, use bridging principles (see 3.10.3.4). 3. If bridging principles do not apply, Sum of concentrations of components classified as Chronic 1, 2, 3 or 4 > 25% 4. For mixtures with no usable information for one or more relevant ingredients, classify using the available information and add the statement: "x percent of the mixture consists of component(s) of unknown hazards to the aquatic environment". 	Hazard statement	May cause long lasting harmful effects to aquatic life
