

Proposal of Corrigendum 6 to the 03 series of amendments to Regulation No. 19

Paragraph 6.4.3., amend to read:

"6.4.3. Photometric requirements

When so adjusted, the front fog lamp shall meet the photometric requirements in the table below (refer also to Annex 4, paragraph 2.2. of this Regulation):

Designated lines or zones	Vertical position */ above h + below h -	Horizontal position */ left of v: - right of v: +	Luminous intensity (in cd)	To comply
Point 1, 2 **/	+ 60°	± 45°	60 max	All points
Point 3, 4 **/	+ 40°	± 30°		
Point 5, 6 **/	+ 30°	± 60°		
Point 7, 10 **/	+ 20°	± 40°		
Point 8, 9 **/	+ 20°	± 15°		
Line 1 **/	+ 8°	- 26° to + 26°	90 max	All line
Line 2 **/	+ 4°	- 26° to + 26°	105 max	All line
Line 3	+ 2°	- 26° to + 26°	170 max	All line
Line 4	+ 1°	- 26° to + 26°	250 max	All line
Line 5	0°	- 10° to + 10°	340 max	All line
Line 6 ***/	- 2.5°	5° inwards to 10° outwards - 10° to + 10°	2,000 min	All line
Line 7 ***/	- 6.0°	5° inwards to 10° outwards - 10° to + 10°	< 50 per cent of max. on line 6	All line
Line 8L and R ***/	-1.5° to - 3.5°	- 22° and + 22°	800 min	One or more points
Line 9L and R ***/	-1.5° to - 4.5°	- 35° and + 35°	320 min	One or more points
Zone D ***/	- 1.5° to - 3.5°	- 10° to + 10°	8,400 max	Whole zone
*/	The co-ordinates are specified in degrees for an angular web with a vertical polar axis.			
**/	See paragraph 6.4.3.4.			
***/	See paragraph 6.4.3.2.			

"

Paragraph 6.4.3.2., amend to read:

"6.4.3.2. At the request of the applicant, two front fog lamps constituting a matched pair corresponding to paragraph 4.2.2.5. may be tested separately. In this case the specified requirements for lines 6, 7, 8, 9 and the Zone D in the table in paragraph 6.4.3. apply to half the sum of readings of the right-hand and left-hand side front fog lamp. However each of the two front fog lamps shall meet at least 50 per cent of the minimum value required for line 6. **Additionally, each of**

the two front fog lamps that constitute the matched pair corresponding to paragraph 4.2.2.5. are only required to meet the requirements of line 6 and line 7 from 5° inwards to 10° outwards.”

Justification

Revision 5, Corrigendum 3 of Regulation 19 has inadvertently introduced a conflict between the horizontal position specified for lines 6 and 7 in paragraph 6.4.3. and the diagram in Annex 4, paragraph 2.2.

The horizontal position specified for lines 6 and 7 in paragraph 6.4.3. (5° inwards to 10° outwards) should only apply to the special case of a matched pair of front foglamps and therefore paragraph 6.4.3.2 should have been amended instead of the table in paragraph 6.4.3.

As the horizontal position requirement of - 10° to + 10° applies in the general case of a front foglamp type approved as a single device, the diagram in Annex 4, paragraph 2.2 is correct.