

**PROPOSAL FOR DRAFT AMENDMENTS TO ECE REGULATION No. 16
(Safety-belts)**

(TRANS/WP.29/GRSP/2001/23)

TRANSMITTED BY EXPERT FROM JAPAN

Background

This document is intended to complete the draft proposal of TRANS/WP.29/GRSP/2001/23.

Note:

Words added to proposed texts in TRANS/WP.29/GRSP/2001/23, are underlined.

*Proposed paragraph 6.4.1.2.5, amend to read:

6.4.1.2.5 In the case of a safety-belt with tension-reducing device, it shall be subjected to a durability test with such a device in operation mode according to paragraph 6.2.5.2.3 or 6.2.5.3.5. before a dynamic test. The dynamic test shall be then conducted on condition that the tension-reducing device is in operation mode.

JUSTIFICATION (6.4.1.2.5)

It is necessary to take into account if the retractor is ALR.

*Paragraph 7.6.4.2, amend to read:

7.6.4.2. Before the dynamic test described in paragraph 7.7 the seated dummy which is clothed with a cotton shirt shall be tilted frontward until 350 mm of the strap withdrawn from retractor, and then release to the initial position.

JUSTIFICATION (7.6.4.2)

This is to adopt the existing requirement of ECE R16.
