

1 July 2020

---

## **Agreement**

### **Concerning the Adoption of Harmonized Technical United Nations Regulations for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these United Nations Regulations\***

(Revision 3, including the amendments which entered into force on 14 September 2017)

---

#### **Addendum 57 – UN Regulation No. 58**

#### **Revision 3 - Amendment 1**

Supplement 1 to the 03 series of amendments – Date of entry into force: 29 May 2020

#### **Uniform provisions concerning the approval of:**

- I. Rear underrun protective devices (RUPDs)**
- II. Vehicles with regard to the installation of an RUPD of an approved type**
- III. Vehicles with regard to their rear underrun protection (RUP)**

This document is meant purely as documentation tool. The authentic and legal binding text is: ECE/TRANS/WP.29/2019/97.



**UNITED NATIONS**

---

\* Former titles of the Agreement:

Agreement concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958 (original version); Agreement concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions, done at Geneva on 5 October 1995 (Revision 2).



*Paragraph 2.4.*, amend to read:

"2.4. Any vehicle of category G will be deemed to satisfy the condition for the ground clearance set out in this Regulation, if the departure angle (ISO 612:1978) does not exceed:

- (a) 10° for vehicles of categories M<sub>1</sub>G and N<sub>1</sub>G;
- (b) 20° for vehicles of categories M<sub>2</sub>G and N<sub>2</sub>G; and
- (c) 25° for vehicles of categories M<sub>3</sub>G and N<sub>3</sub>G;

over a width which is not shorter than that of the rear axle by more than 100 mm on either side (excluding any bulging of the tyres close to the ground).

Where there is more than one rear axle, the width to be considered is that of the widest. The requirements of subparagraphs (a) to (c) of this paragraph shall be satisfied at least on a line:

- (a) At a distance of not more than 450 mm from the rear extremity of the vehicle;
- (b) That may have interruptions summing up in not more than 200 mm."

*PART II. Approval of a vehicle with regard to the installation of an RUPD of an approved type*

*Paragraph 16.1.*, amend to read:

"16.1. For vehicles of the categories N<sub>2</sub> with a maximum mass exceeding 8 t, N<sub>3</sub>, O<sub>3</sub> and O<sub>4</sub>, the ground clearance with respect to the underside of the protective device, even when the vehicle is unladen, shall not exceed:

- (a) 450 mm for motor vehicles and trailers with hydropneumatic, hydraulic or pneumatic suspension or a device for automatic levelling according to load. In any case, a departure angle up to 8° according to ISO 612:1978 with a maximum ground clearance of 550 mm shall be deemed to satisfy the requirements;
- (b) 500 mm for vehicles other than those in (a) above. In any case, a departure angle up to 8° according to ISO 612:1978 with a maximum ground clearance of 550 mm shall be deemed to satisfy the requirements.

This requirement applies over the entire width of the motor vehicle or trailer and shall be such that the height above the ground of the points of application of the test forces applied to the device according to Part I of this Regulation and recorded in the type approval communication form (Annex 1, item 7) does not exceed the values in the paragraphs (a) and (b) above, increased by half the minimum section height required for the cross member of the RUPD.

The height requirement for the application of the test forces shall be adjusted to the adjusted ground clearance due to the provisions for the departure angle specified above."

*PART III. Approval of a vehicle with regard to its rear underrun protection (RUP)*

*Paragraph 25.1.*, amend to read:

"25.1. For vehicles of the categories N<sub>2</sub> with a maximum mass exceeding 8 t, N<sub>3</sub>, O<sub>3</sub> and O<sub>4</sub>, the ground clearance with respect to the underside of the RUP, even when the vehicle is unladen, shall not exceed:

- (a) 450 mm for motor vehicles and trailers with hydropneumatic, hydraulic or pneumatic suspension or a device for automatic levelling according to load;

In any case a departure angle up to 8° according to ISO 612:1978 with a maximum ground clearance of 550 mm shall be deemed to satisfy the requirements.

- (b) 500 mm for vehicles other than those in (a) above. In any case a departure angle up to 8° according to ISO 612:1978 with a maximum ground clearance of 550 mm shall be deemed to satisfy the requirements.

This requirement applies over the entire width of the motor vehicle or trailer and shall be such that the height above the ground of the points of application of the test forces applied to the device according to Part I of this Regulation and recorded in the type approval communication form (Annex 1, item 7) does not exceed the values in subparagraphs (a) and (b) above, increased by half the minimum section height required for the cross member of the RUPD.

The height requirement for the application of the test forces shall be adjusted to the adjusted ground clearance due to the provisions for the departure angle specified above."

Annex 7, table, amend to read:

"

Vehicle category or type of vehicle	Geometry referred to in paragraph			Test force referred to in paragraph(s):
	Section height	Ground clearance before the test	Horizontal distance between the rear of the RUPD and the rear of the vehicle	
M, MG, N <sub>1</sub> , N <sub>1</sub> G, N <sub>2</sub> with a MaxM* < 8 t, N <sub>2</sub> G with a MaxM* < 8 t, O <sub>1</sub> , O <sub>2</sub>	2.3./ 7.1./25.5.	2.3./2.4./ 16.2./25.2.	2.3./ 16.4./25.3.	2.3./ A5/3.1.1. to 3.1.2.
N <sub>2</sub> with a MaxM* > 8 t, N <sub>2</sub> G with a MaxM* > 8 t, N <sub>3</sub> , N <sub>3</sub> G	7.1. or 25.5.	2.4/ 16.1. or 25.1.	16.4. or 25.3.	A5/3.1.1. to 3.1.2.
O <sub>3</sub> , O <sub>4</sub>	7.1. or 25.5.	16.1./16.2. or 25.1./25.2.	16.4. or 25.3.	A5/3.1.1. to 3.1.2.
Specific vehicles (see Annex 6)	7.1. or 25.5.	16.1./16.2. or 25.1./25.2.	16.4. or 25.3.	A5/3.1.3.

\* MaxM means maximum mass.

Note: A reference such as A5/3.1.1. in the table indicates the annex (Annex 5) and paragraph (3.1.1.) of that annex, where the relevant vehicle or requirement is described and specified. A reference such as 2.3. in the table indicates paragraph (2.3.) of this Regulation, where the relevant requirement is specified."